

LED WALL PACK



Ordering Information

Watt	Product Code	Voltage	Color Temp	Lumen	Carton	Dimensions
60W	CL-EWP60-XX-XXK	120-277 OR 480V	5700K	7800	4 PC	14.25"x9.25"x7.36"
80W	CL-EWP80-XX-XXK	120-277 OR 480V	5700K	10400	4 PC	14.25"x9.25"x7.36"
100W	CL-EWP100-XX-XXK	120-277 OR 480V	5700K	13000	4 PC	14.25"x9.25"x7.36"
120W	CL-EWP120-XX-XXK	120-277 OR 480V	5700K	15600	4 PC	14.25"x9.25"x7.36"

480V-UL Driver Stock items are in **BOLD**

DURABLE

Low profile design made of durable die-cast aluminum. Providing good heat sync properties. Designed to give many years of use in the demanding outdoor environment. Protecting from the effects of sun and rain, rust, corrosion, and a finish that resists cracking.

APPLICATION

Ideal for outdoor applications that require good visibility for access and safety.

Workshops	Industrial	Commercial
Warehouses	Toll Booths	Storage Facilities

TECHNICAL DATA

Operating Temp	-15F - 125F
Warranty	5-Yrs
Lifespan	50,000 hrs
Housing	Bronze





