

LED CANOPY



Ordering Information

Watt	Product Code	Voltage	Color Temp	Lumen	Carton	Dimension
40W	CL-ECL-A40-XX-XXK	120-277	5700K	5200	6 PC	10.5"X10.5"X3.3"
60W	CL-ECL-A60-XX-XXK	120-277	5700K	7800	6 PC	10.5"X10.5"X3.3"
80W	CL-ECL-A80-XX-XXK	120-277	5700K	10400	6 PC	10.5"X10.5"X3.3"
120W	CL-ECL-A120-XX-XXK	120-277	5700K	15600	6 PC	12.4"X12.4"X3.8"

Stock items are in **BOLD**

DESCRIPTION

Low profile design made of durable die-cast aluminum. Providing good heat sync properties. Designed to give many years of use in the demanding outdoor environment. Protecting from the effects of sun and rain, rust, corrosion, and a finish that resists cracking.

APPLICATION

Ideal for indoor/outdoor applications that require good visibility for access and safety.

Gyms	Warehouses	Commercial	Entryways
Factories	Workshops	Storage Facilities	Underpasses

TECHNICAL DATA	Operating Temp	-15F - 125F
	Warranty	5-Yrs
	Beam Angle	110 Degree
	Housing	Bronze
	Rating	IP65


